

STUFE A PELLET
 PELLET AIR STOVES
 PELLET-FEU AIR CHAUD
 ESTUFAS A PELET DE AIRE CALIENTE

RIVESTIMENTO IN VETRO
 GLASS COATING
 REVÊTEMENT EN VERRE
 REVESTIMIENTO EN VIDRIO




 magenta

POTENZE DISPONIBILI
 AVAILABLE OUTPUTS
 PUISSANCES DISPONIBLES
 DISPONIBLES EN CAPACIDADES DE
9 KW

DIAMETRO USCITA FUMI
 FLUE OUTLET DIAMETER
 DIAMÈTRE DE SORTIE FUMÉE
 DIAMETRO DEL TUBO DE CHIMENEA
mm 80

DIAMETRO TUBO PRESA D'ARIA
 AIR INTAKE TUBE DIAMETER
 DIAMÈTRE TUBE D'ADMISSION D'AIR
 DIAMETRO DEL TUBO DE VENTILACIÓ
mm 50

CAPACITÀ SERBATOIO
 TANK CAPACITY
 CAPACITÉ DU RÉSERVOIR
 CAPACIDAD DEL DEPÓSITO
kg 16

CONSUMO MEDIO PELLET
 AVERAGE PELLET CONSUMPTION
 CONSOMMATION MOYENNE GRANU
 L'ÉSPROMEDIO DE CONSUMO DE PELLET
kg/h 0,7 ÷ 2,0

POTENZA CALDRICA
 CALORIFIC VALUE
 PUISSANCE DE CHAUFFAGE
 VALOR DE CALEFACCIÓN
kw 9

COLORI DISPONIBILI
 COLOURS AVAILABLE
 COULEURS DISPONIBLES
 COLORES DISPONIBLES

CAPACITÀ DI RISCALDAMENTO
 HEATING CAPACITY
 CAPACITÉ DE CHAUFFAGE
 CAPACIDAD DE CALEFACCIÓN
m³ 260

ASSORBIMENTO
 ABSORPTION
 ABSORPTION
 ABSORCIÓN MW
W 140

PESO
 WEIGHT
 POIDS
 PESO
kg 92

DIMENSIONI
 SIZE
 DIMENSIONS
 DIMENSIONES
 (ALTEZZA x LARGHEZZA x PROFONDITÀ)
 (HEIGHT x WIDTH x DEPTH)
 (HAUTEUR x LARGEUR x PROFONDEUR)
 (ALTURA x ANCHURA x PROFUNDIDAD)
mm 800 (870*) x 820 x 340

RENDIMENTO SUPERIORE A
 EFFICIENCY EXCEEDING
 PERFORMANCE SUPERIOR A
 RENDIMIENTO SUPERIOR A
87%

TELECOMANDO
 REMOTE CONTROL
 TÉLÉCOMMANDE
 MANDO A DISTANCIA
IR

* CON DISPLAY E MANIGLIA
 WITH DISPLAY AND HANDLE
 AVEC ÉCRAN ET POIGNÉE
 CON PANTALLA Y MANILLA

